



Farabaugh Engineering and Testing LLC.

Project No. T320-25

Report Date: November 18, 2025

No. Pages: 16 (inclusive)

PERFORMANCE TEST REPORT

ALUMINUM HANDRAIL SYSTEM

FOR

SHAPES UNLIMITED, INC.
590 E. WESTERN RESERVE RD.
YOUNGSTOWN, OH 44514

Report Prepared By:

Daniel C. Farabaugh

Reviewed and Approved By:

Daniel G. Farabaugh

Purpose

This testing was performed to evaluate the referenced test specimens under various load conditions as provided herein.

Test Specimen

Manufacturer: Shapes Unlimited, Inc.
590 E. Western Reserve Rd.
Youngstown, OH 44514

Specimen: - Standard Residential and Commercial Hand Rail Panel
- Nominal 8' long x 42-1/4" High
- Continuous Rail with Rail Bracket (attached to aluminum post 3"x 3" x 48")
- 1" X 1" aluminum balusters (pickets) at 5" oc

Testing Apparatus

The test apparatus consisted of a panel mock-up assembly (3 aluminum posts and 2 handrail panels) and load applicator. The mock-up assembly was as shown on the attached detail drawings. The loads were measured with a calibrated load cell. The loads were applied to specific components as shown on the attached drawing. The base of each aluminum post was secured so that the connection between the post base flange and the test fixture was excluded from the scope of this test.

Test Procedure

The specimen was loaded at a rate to achieve the specified loads between 10 seconds and 5 minutes. The specified test loads were held for one minute before the load was released.

In-fill Load Test

- A 50 lb load was applied at the mid-span center of the panel balusters over a 1 ft² area, perpendicular to the in-fill.

Uniform Load Tests

- A 50 lb/ft uniform load (using the 1/4-point load method) was applied across the top rail, first in a vertical downward direction and then separately in a horizontal direction. The loads were applied simultaneously across both panels.

Concentrated Load Tests

- At the mid-span of the top rail, loads were applied in both vertical downward and horizontal directions, with the loads applied simultaneously across both panels.
- Additionally, a concentrated load was applied at the top of both the end post and the interior post separately.

TEST DATA

Testing Date: 10-22-25

In-fill Load Test

MEMBER	LOCATION	TEST LOAD	LOAD DIRECTION
Balusters	Center Midspan (1 SF Area)	50 lb	Horizontal

Results:

As a result of the above loading, there were no noticeable failures of the specimen.

Uniform Load Test (using ¼ point loading method)

MEMBER	LOCATION	TEST LOAD	LOAD DIRECTION
Top Rail	Across Top Rail	50 lb/ft	Vertically Downward
Top Rail	Across Top Rail	50 lb/ft	Horizontal

Results:


As a result of the above loading, there were no noticeable failures of the specimen.

Concentrated Load Test


MEMBER	LOCATION	TEST LOAD	LOAD DIRECTION
Top Rail	Mid-span Between Posts	200 lb	Vertically Downward
Top Rail	Mid-span Between Posts	200 lb	Horizontal
Interior Post	Top of Post	200 lb	Horizontal
End Post	Top of Post	200 lb	Horizontal

Results:


As a result of the above loading, there were no noticeable failures of the specimen.




ELEVATION VIEW




DETAIL "A"




DETAIL "B"





 PT. SIDO AGUNG ALUMI design@sidoagungalumi.com		SECTION No. GCA-0086 00367 MATTING WITH SECTION																																			
SHA		F. E. T. INC. Review for general compliance with test report AS NOTED ONLY BY: <u>DCF</u> PROJECT # <u>T320-25</u>																																			
																																					
<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <th colspan="2">INSPEC. DIMENSION ACCORDING TO THIS TOLERANCES</th> </tr> <tr><td><1</td><td>±0.10</td></tr> <tr><td><1-2</td><td>±0.12</td></tr> <tr><td><2-3</td><td>±0.14</td></tr> <tr><td><3-4</td><td>±0.16</td></tr> <tr><td><4-6</td><td>±0.18</td></tr> <tr><td><6-12</td><td>±0.20</td></tr> <tr><td><12-19</td><td>±0.23</td></tr> <tr><td><19-25</td><td>±0.25</td></tr> <tr><td><25-38</td><td>±0.30</td></tr> <tr><td><38-50</td><td>±0.36</td></tr> <tr><td><50-100</td><td>±0.61</td></tr> <tr><td><100-150</td><td>±0.86</td></tr> <tr><td><150-200</td><td>±1.12</td></tr> <tr><td><200-250</td><td>±1.38</td></tr> </table>		INSPEC. DIMENSION ACCORDING TO THIS TOLERANCES		<1	±0.10	<1-2	±0.12	<2-3	±0.14	<3-4	±0.16	<4-6	±0.18	<6-12	±0.20	<12-19	±0.23	<19-25	±0.25	<25-38	±0.30	<38-50	±0.36	<50-100	±0.61	<100-150	±0.86	<150-200	±1.12	<200-250	±1.38	NOTE: — — EXPOSED REMOVE SHARP CORNERS WITH 0.41mm RADIUS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td style="width: 30%;">C.C.D</td> <td>Ø 107.42</td> </tr> <tr> <td>CEXPOSED SURFACE</td> <td>P/C</td> </tr> </table> ALUMINUM ASSOCIATION STANDARD EXTRUSION TOLLERANCES WILL APPLY UNLESS OTHERWISE NOTED ON PRINT		C.C.D	Ø 107.42	CEXPOSED SURFACE	P/C
INSPEC. DIMENSION ACCORDING TO THIS TOLERANCES																																					
<1	±0.10																																				
<1-2	±0.12																																				
<2-3	±0.14																																				
<3-4	±0.16																																				
<4-6	±0.18																																				
<6-12	±0.20																																				
<12-19	±0.23																																				
<19-25	±0.25																																				
<25-38	±0.30																																				
<38-50	±0.36																																				
<50-100	±0.61																																				
<100-150	±0.86																																				
<150-200	±1.12																																				
<200-250	±1.38																																				
C.C.D	Ø 107.42																																				
CEXPOSED SURFACE	P/C																																				
<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td style="width: 20%;">No. REF.</td> <td>01-M1-170221</td> </tr> <tr> <td>DATE</td> <td>FEBRUARY 17th, 2021</td> </tr> <tr> <td>SCALE</td> <td>1 : 1</td> </tr> <tr> <td>DRAWN</td> <td>YB 17_02_2021</td> </tr> <tr> <td>CHECKED</td> <td>17_02_2021</td> </tr> <tr> <td>EST. AREA</td> <td>878.4 mm²</td> </tr> <tr> <td>EST. WEIGHT</td> <td>1.611 WT/FT</td> </tr> <tr> <td>EST. PERIMETER</td> <td>304.096 mm</td> </tr> <tr> <td>P.C. PERIMETER</td> <td>- mm</td> </tr> </table>		No. REF.	01-M1-170221	DATE	FEBRUARY 17th, 2021	SCALE	1 : 1	DRAWN	YB 17_02_2021	CHECKED	17_02_2021	EST. AREA	878.4 mm ²	EST. WEIGHT	1.611 WT/FT	EST. PERIMETER	304.096 mm	P.C. PERIMETER	- mm	<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td style="width: 20%;">DIMENSI</td> <td>76.20 X 76.20</td> </tr> <tr> <td>THICKNESS</td> <td>3.00 [0.118"]</td> </tr> <tr> <td>TOLERANCE</td> <td>± 0.18mm [0.007"]</td> </tr> <tr> <td>ALLOY & TEMPER</td> <td>6063-T6</td> </tr> <tr> <td>EXTRUDE RATIO</td> <td>-</td> </tr> <tr> <td>BILLET</td> <td>7"</td> </tr> <tr> <td>MACHINE MODEL</td> <td>700 T ☐ 1000 T ☐ 1800 T ☒</td> </tr> </table>		DIMENSI	76.20 X 76.20	THICKNESS	3.00 [0.118"]	TOLERANCE	± 0.18mm [0.007"]	ALLOY & TEMPER	6063-T6	EXTRUDE RATIO	-	BILLET	7"	MACHINE MODEL	700 T ☐ 1000 T ☐ 1800 T ☒		
No. REF.	01-M1-170221																																				
DATE	FEBRUARY 17th, 2021																																				
SCALE	1 : 1																																				
DRAWN	YB 17_02_2021																																				
CHECKED	17_02_2021																																				
EST. AREA	878.4 mm ²																																				
EST. WEIGHT	1.611 WT/FT																																				
EST. PERIMETER	304.096 mm																																				
P.C. PERIMETER	- mm																																				
DIMENSI	76.20 X 76.20																																				
THICKNESS	3.00 [0.118"]																																				
TOLERANCE	± 0.18mm [0.007"]																																				
ALLOY & TEMPER	6063-T6																																				
EXTRUDE RATIO	-																																				
BILLET	7"																																				
MACHINE MODEL	700 T ☐ 1000 T ☐ 1800 T ☒																																				
00367		<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td colspan="4" style="text-align: center;">APPLICATION</td> </tr> <tr> <td colspan="4" style="text-align: center;">SQUARE HOLLOW</td> </tr> <tr> <td colspan="4" style="text-align: center;">PRODUCT CLASSIFICATIONS</td> </tr> <tr> <td style="text-align: center;">SOLID ☐</td> <td style="text-align: center;">SEMIHOLLOW ☐</td> <td style="text-align: center;">HOLLOW ☒</td> <td style="text-align: center;">SPECIAL ☐</td> </tr> </table>		APPLICATION				SQUARE HOLLOW				PRODUCT CLASSIFICATIONS				SOLID ☐	SEMIHOLLOW ☐	HOLLOW ☒	SPECIAL ☐																		
APPLICATION																																					
SQUARE HOLLOW																																					
PRODUCT CLASSIFICATIONS																																					
SOLID ☐	SEMIHOLLOW ☐	HOLLOW ☒	SPECIAL ☐																																		

Aluminum Post







Post Base Flange

PART #	FINISH	COLOR	L*	a*	b*	G*
NW6259-SBL	SANDBLASTED	MILL	-	-	-	-
NW6259-BK	POWDER COAT	BLACK	24	0	0	35
NW6255-WZ	POWDER COAT	WHITE	95	-1.4	1.5	80
NW6259-BZ	POWDER COAT	BROWN	34	0.5	2.1	75
NW6255-BZ2	POWDER COAT	BRONZE 2	36	0.7	3.5	58



SECTION A-A



F. E. T. INC.
Review for general compliance
with test report AS NOTED ONLY
BY: DCF
PROJECT # T320-25

REVISIONS			
ECR/OCR	REV.	DESCRIPTION	DATE
-	-	INITIAL RELEASE	11/5/15


 NATIONWIDE INDUSTRIES		"BREAD LOAF" SINGLE FLANGE WALL MOUNT BRACKET	
SIZE DIM. CS - NW6259 A. NO. 1 ARCH. W/WH.		REV. 1 SHEET 1 OF 1	
DRAWING NAME DATE CHECKED BY BIG INCH MFG. APPR.		Q.A. COMMENTS	
ORDERED BY & PROJ. NO. PROJECT NO. MATERIAL 4380 CAST ALUMINUM FINISH		DO NOT SCALE DRAWING	

Top Rail Mounting Bracket



Part #	Finish:	Color
NW243-SBL	SANDBLASTED	-
NW243-BK	POWDER COATED	BLACK
NW243-WH	POWDER COATED	WHITE
NW243-BZ	POWDER COATED	Bronze

ECRDCR	REV.	DESCRIPTION	DATE	APPL
-	-	INITIAL RELEASE	03-29-19	DDC

Technical drawing of a rectangular plate. The overall dimensions are 3.63 (width) and 1.66 (height). The central rectangular area has a width of 3.00 and a height of 1.66. There are two circular holes, one in the top flange and one in the bottom flange. The bottom hole is labeled "2X Ø.27 THRU".



F. E. T. INC.
Review for general compliance
with test report AS NOTED ONLY
BY: DCF
PROJECT # T326-25




MATERIAL: A360 ALUMINUM

NATIONWIDE
INDUSTRIES

**DUAL FLANGE
WALL MOUNT BRACKET**


DRAWING IS IN UNITS DIMENSIONS (I/F) TOLERANCES (F/M) ASSUME MACHINING IS UNLESS OTHERWISE SPECIFIED SHEET A OF TOTAL 2.0005		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NATIONAL WIDELINE INDUSTRIES AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF NATIONAL WIDELINE INDUSTRIES	
DUAL FLANGE WALL MOUNT BRACKET 1-5/8" X 1-5/8" CS-NW243		SEE DWG. A FINISHES WEIGHT	
SHEET OF 1		REVISIONS	

Bottom Rail Mounting Bracket




Top Rail

F. E. T. INC.
Review for general compliance
with test report AS NOTED ONLY
BY: **DCF**
PROJECT # **T320-25**




Bottom Rail



Bottom Rail



373



F. E. T. INC.
Review for general compliance
with test report AS NOTED ONLY
BY: DCF
PROJECT # T320-25

Baluster (Picket)

SHAPES

UNLIMITED

ALUMINUM BUILDING PRODUCTS

3" x 3" #367 Aluminum Post with Welded Floor Mount


Configuration: SHAPES 3x3 #367 Post welded to NW6173 Floor Mount Base

Post Dimensions: 3.000" x 3.000" (0.125" wall thickness)
 Flange Dimensions: 5.37" x 5.37" base, 1.75" height, Ø0.225" holes (4x)
 Insert depth: 3.029" typ. Total assembly height: 4.78" typ.
 Material: Post - 6063-T5 Aluminum | Flange - Cast Aluminum (A356-T6 or eq.)
 Finish: Powder Coat (Black, White, Bronze, or Mill)

F. E. T. INC.
 Review for general compliance
 with test report AS NOTED ONLY

BY: DCF

PROJECT # T320-25




Base Plate 5.37" x 5.37"



NOTES:

1. Weld continuously along full perimeter of post-to-base connection.
2. Fillet Weld ¼" using Lincoln SuperGlaze 4043 Mig Wire
3. Remove weld spatter and sharp edges prior to coating.
4. Anchor assembly designed by others.
5. Assembly intended for surface-mount applications.
6. Dimensional tolerances ±0.03" unless otherwise noted.



| REV: A | DATE: NOV 2025 |

Post/ Base Flange Connection

Revision Log

<u>Rev. #</u>	<u>Date</u>	<u>Page(s)</u>	<u>Revision (s)</u>
0	November 18, 2025	16	Original Report Issue

*This report is confidential and exclusively intended for FET's Client as per the agreement between FET and its Client. FET is responsible only within the terms and conditions of the agreement and assumes no liability to any other party for any loss, expense or damage arising from the use of this report. The report may be copied or distributed only with the Client's authorization and in its entirety, and the observations and test results are relevant only to the specific sample tested. All components of the test specimens were aluminum, with the exception of fasteners. Verification of the specific aluminum alloy was **not** part of the scope of this testing.*