

SHAPES Unlimited Inc.

Wholesale Aluminum Trim Coil for Professional Window Finishing

Professional Finish

Whether it's a new build or a replacement project, a flawless exterior trim is the difference between "installed" and "complete." Without trim coil, a window install can look unfinished, be vulnerable to water intrusion, and hurt curb appeal. SHAPES Unlimited Aluminum Trim Coil gives installers the speed, protection, and clean look they need — without the maintenance headaches of painted wood.

Why Use SHAPES Trim Coil for Windows?

- Weather Protection – Shields wood casings, brickmolds, and sills from rot, warping, and peeling paint.
- Maintenance-free beauty – No painting, no staining, no scraping.
- Custom Fit On-Site – Bend and cut for a perfect wrap, every time.
- Seamless Style – Matches today's top siding and window frame colors.



DON'T PAINT

Finishing Any Project

Smooth Finish – Sleek, modern look ideal for sharp lines and contemporary window designs. Polyester or acrylic coating resists tool marks during bending/installation.

Textured (PVC-Coated) Finish – Subtle striations mimic wood grain for a warmer, traditional feel. Thicker, PVC-infused coating stands up to pollution, salt air, and acid rain.

Performance You Can Count On

- Standard Thickness: Nominal 0.019" for everyday window wraps
- Heavy-Duty Option :Nominal 0.024" for deep jambs, large picture windows, and high-wind areas
- Color-Matched Selection: Wide palette to blend or contrast with siding, fascia, or soffit
- Precision Forming: Crisp hems and bends without cracking paint
- Crisp white backing - dual-color options.
- Unique side-load boxes



Installation Best Practices

- Allow for Expansion – Avoid over-tight nailing; pre-drill oversized holes if needed.
- Hem for Strength – Hemmed edges increase rigidity and give a polished appearance.
- Use Proper Fasteners – Aluminum or stainless-steel nails only.
- Minimize Face-Nailing – Tuck top edges under drip caps or head flashings.
- Protect Against Corrosion – Use a barrier layer when wrapping pressure-treated wood.

Product Specs (Mix Colors on Pallets)

Roll Size	Smooth & PVC Half Truck	Smooth & OVC Full Truck	Available Thickness
24" x 50"	576 Rolls - 18 Pallets	1,152 Rolls - 36 Pallets	0.019" 0.024"


Contact SHAPES Unlimited Inc.

Phone: 330.726.0844 | Website: www.shapesunlimitedinc.com | Email: customerservice@shapesunlimited.net
13001 Mahoning Avenue, North Jackson, Ohio 44451

Smooth and PVC Color Selection Guide

- 280 White – Smooth
- Lomar White – Smooth & PVC
- Black – Smooth & PVC
- Royal Brown – Smooth & PVC
- Terra Bronze – Smooth
- Black/Black – Smooth
- Black/Royal Brown – Smooth
- Black/Terra Bronze - Smooth

For all other colors, Smooth or PVC availability, please reach out to your sales representative.



TRIM COIL COLORS									
Colonial White*	Bright White*	280 White	Snow White*	Lomar White*	Sandstone Beige*	Pearl	Bone Linen	Heritage Cream*	
Autumn Yellow*	Wheat	Herringbone*	Almond	Light Maple*	Sandpiper	Desert Tan*	Savannah Wicker*	Saddle	
Rye	Herringbone A	Desert Sand	Pebblestone Clay*	Natural Clay*	Buckskin	Terra Cotta	Mountain Cedar	Autumn Red	
Lighthouse Red	Royal Brown*	Musket Brown A*	Musket Brown	Musket Brown C*	Dark Bronze	AMP Dark Bronze*	Montana Suede	Sable Brown*	
Terra Bronze	Granite Gray*	Victorian Gray	Glacier Blend	Charcoal Gray	Pearl Gray	Silver Ash	Greystone	Tuxedo Gray*	
Harbor Gray	Sand NX	Sterling Gray*	Silver Gray	Oxford Blue*	Deep Granite	Black*	Regatta Blue	Portsmouth Blue	
Pacific Blue*	Bermuda Blue	Harbor Blue	Flagstone	Ivy Green	Seagrass	Quiet Willow	Hearthstone	Suede	
Spruce	Forest	Greelan Green*	Rugged Canyon	Green Tea	Tuscan Olive	Cypress			

*.024" only available in Black/Royal Brown or Snow White/Alcoa Musket Brown

Trim Coil Specifications

PVC		
Metal Specifications	Alloy	3105 H18/H28 temper
	Gauge	.0165" +/- .00075" before paint
	Width	23.9375" +/- .0312"
	Tensile Strength	28,000 psi
	Yield Strength	24,000 psi
Paint Specifications	Top Coating	Plastisol
	Film Thickness	3.5 mils – wet
	Adhesion	Excellent, ASTM test D3359
	Gloss	20-50 @ 60 degrees
Smooth Trim Coil (all colors)		
Metal Specifications	Alloy	3105 H18/H28 temper
	Gauge	.0165" +/- .00075" before paint
	Width	23.9375" +/- .0312"
	Tensile Strength	28,000 psi
	Yield Strength	24,000 psi
Paint Specifications	All colors meet standards specified in AAMA report 1402.86	
	Coating	Polyester
	Film Thickness	.60-.80 mils each side
	Adhesion	Excellent, ASTM test D3359
	Gloss	10-20 @ 60 degrees



Contact SHAPES Unlimited Inc.

Phone: 330.726.0844 | Website: www.shapesunlimitedinc.com | Email: customerservice@shapesunlimited.net
13001 Mahoning Avenue, North Jackson, Ohio 44451